

Подкласс	Тип шва	Кол-во игл	Кол-во ниток	Используемые иглы		Расстояние между иглами (дюймы)	Макс. Длина стежка (мм)	Диффе- ренциал	Высота подъёма лапки (мм)	Ход игловодителя (мм)	Скорость (об/мин)
		Organ (#)	Schmetz (Nm)								
											
BX1425P	401	25	50	UOx113 14	UYx113 90	1/4	3,0		10	34	2500
BX1425PS	401	25	50	DVx57 14	DVx57 90	1/4	3,5		10	34	2500
BX1425PSM	401	25	75	DVx57 14	DVx57 90	1/4	3,5		6	34	2000
BX1425PSSM	401	25	75	DVx57 14	DVx57 90	1/4	3,5		6	34	2000
BX1433P	401	33	66	UOx113 14	UYx113 90	3/16	3,5		10	34	2500
BX1433PS	401	33	66	DVx57 14	DVx57 90	3/16	3,5		10	34	2500
BX1433PSM	401	33	99	DVx57 14	DVx57 90	3/16	3,5		6	34	2000
BX1433PSSM	401	33	99	DVx57 14	DVx57 90	3/16	3,5		6	34	2000
BX1025P	101	25	25	DV-K25 21		1/4	3,5		10	34	2500
BX1025PS	101	25	25	DV-K25 21		1/4	3,5		10	34	2500
BX1025PSM	101	25	50	DV-K25 21		1/4	3,5		6	34	2000

BX1033P	101	33	33	DV-K25 21		3/16	3,5		10	34	2500
BX1033PS	 101	33	33	DV-K25 21		3/16	3,0		10	34	2500
BX1033PSM	101	33	33	DV-K25 21		3/16	3,0		6	34	2000
BX1425PET	401	25	50	DVx57 14	DVx57 90	1/4	3,5		10	34	2500
BX1425PSET	401	25	50	DVx57 14	DVx57 90	1/4	3,5		10	34	2500
BX1425PSMET	401	25	75	DVx57 14	DVx57 90	1/4	3,5		6	34	2000
BX1425PSSMET	401	25	75	DVx57 14	DVx57 90	1/4	3,5		6	34	2000
BX1433PET	401	33	66	DVx57 14	DVx57 90	3/16	3,5		10	34	2500
BX1433PSET	401	33	66	DVx57 14	DVx57 90	3/16	3,5		10	34	2500
BX1433PSMET	401	33	99	DVx57 14	DVx57 90	3/16	3,5		6	34	2000
BX1433PSSMET	401	33	99	DVx57 14	DVx57 90	3/16	3,5		6	34	2000