

Subclass	Application	Fabric weight	Type of needle	No,of needles	No,of threads	Needle space	Overedge width	Stitch length	Feed dog type	Pitch of feed dog	Diff,Feed ratio	Presser foot lift	Max speed	Remarks
			DCx27			mm	mm	mm		mm		mm	rpm	
														
UK1004S-01M-4 [SEAM TYPE]	plain seaming	light to medium	#11	1	3	-	4	1~3.8		1.6	0.7~2	6	6500	
UK1005S-10M-3	hemming	light to medium	#9	1	3	-	3	1~3.8		1.6	0.7~2	6	6500	
UK1005S-10M-4	hemming	light to medium	#9	1	3	-	4	1~3.8		1.6	0.7~2	6	6500	
UK1004S-20F-1 [SEAM TYPE]	turn down hemming	light to medium	#9	1	3	-	1.5	1~3.8		1.6	0.7~2	6	6500	
UK1004S-50M-3 [SEAM TYPE]	backlatching	light to medium	#11	1	3	-	3	1~3.8		1.6	0.7~2	6	6500	
UK1004S-50M-4 [SEAM TYPE]	backlatching	light to medium	#11	1	3	-	4	1~3.8		1.6	0.7~2	6	6500	


2 NEEDLE OVERLOCK MACHINE

Subclass	Application	Fabric weight	Type of needle	No,of needles	No,of threads	Needle space	Overedge width	Stitch length	Feed dog type	Pitch of feed dog	Diff,Feed ratio	Presser foot lift	Max speed	Remarks
			DCx27			mm	mm	mm		mm		mm	rpm	
														

UK1014H-01M-2x4 [SEAM TYPE]	plain seaming	light to medium	# 11	2	4	2	4	1~3.8		1.6	0.7~2	6	6500	
UK1014H-01M-2x5 [SEAM TYPE]	plain seaming	light to medium	# 11	2	4	2	5	1~3.8		1.6	0.7~2	6	6500	
UK1014H-40M-2x4	tape binding	light to medium	# 11	2	4	2	4	1~3.8		1.6	0.7~2	6	6500	
UK1014H-40M-2x5	tape binding	light to medium	# 11	2	4	2	5	1~3.8		1.6	0.7~2	6	6500	
UK1014H-50M-2x4 [SEAM TYPE]	backlatching	light to medium	# 11	2	4	2	4	1~3.8		1.6	0.7~2	6	6500	
UK1014H-50M-2x5 [SEAM TYPE]	backlatching	light to medium	# 11	2	4	2	5	1~3.8		1.6	0.7~2	6	6500	

2 NEEDLE SAFETY STITCH MACHINE

Subclass	Application	Fabric weight	Type of needle	No,of needles	No,of threads	Needle space	Overedge width	Stitch length	Feed dog type	Pitch of feed dog	Diff,Feed ratio	Presser foot lift	Max speed	Remarks
			DCx27			mm	mm	mm		mm		mm	rpm	
														
UK1116S-01M-3x4 [SEAM TYPE]	plain seaming	light to medium	# 11	2	5	3	4	1~3.8		1.6	0.7~2	6	6500	
UK1116S-02M-3x4 [SEAM TYPE]	plain seaming	light to medium	# 11	2	5	3	4	1~3.8		1.6	0.7~2	6	6500	foot for tubular structure

UK1116S-01H-5x5 [SEAM TYPE]	plain seaming	heavy	#11	2	5	5	5	1~3.8		1.6	0.7~2	6	6500	
UK1116H-03X-5x5 [SEAM TYPE]	plain seaming	ultra heavy	#21	2	5	5	5	1~5		2.5	0.7~1.4	7	5500	tractor foot
UK1116H-03X-5x6 [SEAM TYPE]	plain seaming	ultra heavy	#21	2	5	5	6	1~5		2.5	0.7~1.4	7	5500	tractor foot
UK1116S-30M-3x4 [SEAM TYPE]	gathering	light to medium	#11	2	5	3	4	1~3.2		1.6	0.8~3	6	5500	
UK1116S-30M-5x5	gathering	light to medium	#11	2	5	5	5	1~3.2		1.6	0.8~3	6	5500	

3 NEEDLE SAFETY STITCH MACHINE

Subclass	Application	Fabric weight	Type of needle	No,of needles	No,of threads	Needle space	Overedge width	Stitch length	Feed dog type	Pitch of feed dog	Diff,Feed ratio	Presser foot lift	Max speed	Remarks
			DCx27			mm	mm	mm		mm		mm	rpm	
														
UK1143H-90M-3x2x4 [SEAM TYPE]	plain seaming	light to medium	#11	3	6	3x2	4	1~3.8		1.6	0.7~2	6	6000	